

NEW PRODUCTS NP-158

DC / DC DC24V → DC12V CONVERTER



Photo: DDS-230

Product lineup	
DDH-203	→ (Max 3A)
DDH-205	→ (Max 5A)
DDS-208	→ (Max 8A)
DDS-212	→ (Max 12A)
DDS-220	→ (Max 20A)
DDS-230	→ (Max 30A)

FEATURES


- Ultra slim and compact body
- Control signal voltage converting circuit: 3 lines
(Control signal: Illumination, Parking brake, Reverse, etc)
- High capacity continuous output (Back-up output)
- Interlock output with ACC (Key switch)
- High conversion efficiency by switching system



<http://www.newera.co.jp/>

New-Era Co., Ltd.



<p>New</p> <p>DDH-203</p> <p>Max 3A</p>		<p>Protection against input reverse connection Protection against output over current Protection against input output reverse connection(*) Vibration resistance: 8.3~400Hz 6.8G, JASO standard Water proof: D0203 D2, JIS standard Height: 42mm Weight: 300g</p>
<p>New</p> <p>DDH-205</p> <p>Max 5A</p>		<p>Protection against input reverse connection Protection against output over current Protection against input output reverse connection(*) Vibration resistance: 8.3~400Hz 6.8G, JASO standard Water proof: D0203 D2, JIS standard Height: 42mm Weight: 450g</p>
<p>DDS-208</p> <p>Max 8A</p>		<p>Protection against input reverse connection (Fuse) Protection against output over current Height: 37mm Weight: 600g Control signal voltage: 3 lines</p>
<p>DDS-212</p> <p>Max 12A</p>		<p>Protection against input reverse connection (Fuse) Protection against output over current Height: 37mm Weight: 620g Control signal voltage: 3 lines</p>
<p>New</p> <p>DDS-220</p> <p>Max 20A</p>		<p>Protection against input reverse connection Protection against output over current Protection against input output reverse connection(*) Height: 44.5mm Weight: 1180g Control signal voltage: 3 lines</p>
<p>New</p> <p>DDS-230</p> <p>Max 30A</p>		<p>Protection against input reverse connection Protection against output over current Protection against input output reverse connection(*) Height: 44.5mm Weight: 1520g Control signal voltage: 3 lines</p>

(*) to connect 24V input cable to 12V output terminal

Installable vehicles (24V vehicles): Truck, Bus, Excavator, Crane, Boat, etc.

Usable equipments (12V accessories):

car navigation, radio, car stereo, TV, DVD, radio transmission, radio detector, accessory lamp, electric reel, etc.